BERKELEY® B3TPMS Silicon Bronze Impeller


Threaded Case (NPT), Mechanical Shaft Seal Construction

ELECTRIC MOTOR DRIVE

Section	CC
Page	160.21
Date	March 4, 2013
Supe	rsedes 01/01/04

Table I

B/M No.	HP	PH	RPM	"U" Dim.	Imp. Dia.	Imp. No.
B74806	1	1	1800	7/8"	5.12"	L08174
B74807	1	3	1800	7/8"	5.12"	L08174
B74809	1.5	1	1800	7/8"	5.75"	L08172
B74810	1.5	3	1800	7/8"	5.75"	L08172
B74812	2	1	1800	7/8"	6.25"	L08168
B74813	2	3	1800	7/8"	6.25"	L08168
B74815	3	1	1800	7/8"	6.50"	L08169
B74816	3	3	1800	7/8"	6.50"	L08169



Item No.	Part Description	Part Number L01104	
1	Case, Volute		
2	Impeller	See Table I	
14	Sleeve, Shaft	S19310L	
26	Screw, Impeller 3/8 - 16 x 1"	S23566	
32	Key, 3/16 x 1-1/4" (See Note)	S34383	
69	Washer, Impeller	S06314	
71	Bracket	See Table II	
73	Gasket, Volute	S04757	
89	Seal, Mechanical Shaft	S32014	
800	Capscrew, 3/8 - 16 x 1" (4 Req.)	S26826	
801	Stud, 1/2 - 13 x 1-1/2" [4 Req.]	S24043	
802	Nut, 1/2 - 13 (4 Req.)	S23107	
805	Washer, Lock	S23036	
810	Plug, Pipe 1/4" NPT (5 Req.)	S23715	
815	Ring, Retaining	S11207	
•	Plug, Pipe 1/8" NPT (In Bracket)	S23714	

Not illustrated.

Table II

HP	PH	Bracket No.	"AK" Fit	"U" Dim.	Motor Frame				
1	1	L05329	4-1/2"	7/8"	143JM				
1	3	L05329	4-1/2"	7/8"	143JM				
1.5	1	L05329	4-1/2"	7/8"	145JM				
1.5	3	L05329	4-1/2"	7/8"	145JM				
2	1	L05329	4-1/2"	7/8"	182JM				
2	3	L05329	4-1/2"	7/8"	145JM				
3	1	L05329	4-1/2"	7/8"	184JM				
3	3	L05329	4-1/2"	7/8"	182JM				

NOTE 1: For an explanation of the tabulated material found on this page and for impeller key location, refer to **Supplement A** located at the beginning of this section.

NOTE 2: For seal flush line details, see Supplement D.

